



HENKEL Australia Pty Ltd  
A.C.N. 001 302 996

135-141 Canterbury Road  
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200  
Fax: (03) 9728 5877  
Customer Service 1300 736 777

Distributed by  
Solvents Australia Pty Ltd  
ABN 74 003 523 117  
77 Bassett Street  
Mona Vale NSW 2100  
PO Box 928  
Mona Vale NSW 1660

Tel: (02)9979 6866  
Fax: (02)9979 6864

---

## Technical Data Bulletin

---

### TURCO 5351 THIN

Material. No. 378409

### TANK TYPE EPOXY AND POLYURETHANE REMOVER

#### **DESCRIPTION:**

TURCO 5351 THIN is an amber, diphasic liquid developed to remove epoxy, polyurethane and other catalysed finishes from ferrous and non-ferrous surfaces. The product contains no free acidic or alkaline constituents and is approved for use on Aluminium, Magnesium and high strength steels.

TURCO 5351 THIN should not be used on materials that are affected by chlorinated hydrocarbons.

#### **BENEFITS:**

TURCO 5351 THIN offers the following benefits:

1. Non-flammable.
2. Used at ambient temperatures.
3. Used as received. No mixing or dilution required.
4. Comes with built-in seal.
5. Seal is maintained by addition of tap water.
6. Freely rinses from parts with high pressure, high volume cold water.

#### **USE INSTRUCTIONS:**

**TANKS:** Tanks and associated equipment may be fabricated from mild steel or stainless steel. Stainless steel is preferred.

**CONCENTRATION:** Use at full strength, as received.

**APPLICATION:** Immerse parts into stripper, below the seal layer. Seal layer retards evaporation

of solvents and does not have stripping capabilities. Allow sufficient time for stripper to loosen finish.

**RINSE:** Remove parts from stripper tank and rinse with high volume, high pressure cold water.

**SEAL MAINTENANCE:** The seal layer is gradually depleted through evaporation and dragout. Maintain seal layer at a depth of 100 mm by addition of clean, cold water.

**STRIPPER CONTROL:** Normal adjustments will require top-up only, but extended heavy use may also require additions of solvent. Refer to your ATOFINA REPRESENTATIVE.

### **DISPOSAL INFORMATION:**

Dispose of spent stripper per local, state and regional regulations. Refer to your local HENKEL REPRESENTATIVE or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

### **CAUTION:**

TURCO 5351 THIN remover contains chlorinated hydrocarbons, phenol and chromate. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid prolonged breathing of vapours. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, apron and boots made from a solvent resistant neoprene should be worn when handling and using this product.

Containers exposed to moderate heat, above 32°C may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional handling, precautionary and first aid information.

JUNE, 2002

® Registered Tradename HENKEL Australia Pty Ltd  
© Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: [admin@solvents.net.au](mailto:admin@solvents.net.au)