



HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO 6840S

Material No. 377685

WATER BASED ENVIRONMENTALLY ADVANTAGED PAINT REMOVER

DESCRIPTION:

TURCO 6840S is a viscous, light purple liquid formulated to remove multiple coats of paints, such as baked enamels, lacquers, varnish, synthetic enamels, Koroflex, polysulphide, zinc chromate primers, epoxies and polyurethanes.

TURCO 6840S paint remover clings to vertical as well as over-head surfaces and can be used on aluminium, magnesium, cadmium-plated steels and other ferrous metals.

FEATURES:

TURCO 6840S paint remover offers these features:

1. Very low odour.
2. Non-flammable.
3. Free of phenols, acids, chlorinated hydrocarbons and heavy metals.
- 4 Readily rinses with cold water.
- 5 Can be applied by nonatomising spray, or brush.
6. Used as received. No mixing or dilution required.
- 7.Passes all essential requirements of MIL-R-25134B, C.S.D. #1, and D6-17487.
8. Passes "effects on metals" portion of MIL-R-81294C.

USE INSTRUCTIONS:

Best results are obtained if hangar is preheated to 30-40°C.

Application: Apply by brush or nonatomising spray methods to surface requiring stripping. Apply a smooth, even coat and allow sufficient dwell time for remover to penetrate and loosen paint. When paint is loosened, thoroughly agitate the surface with a stiff bristle brush. If paint adheres to specific areas, just allow additional dwell time before rinsing. TURCO 6840S remains active for several hours. Additional application may be necessary for some particularly stubborn and/or over coated areas.

Removal: Spent TURCO 6840S and paint residues may be squeezed off or rinsed with high pressure, high volume water. Brushing during operation assists in removal of all residues.

NOTE: TURCO 6840S may attack plastics, rubber seals and tires. These materials should be protected.

CAUTION! May cause irritation to skin and eyes. May be harmful if swallowed.

TURCO 6840S paint remover contains nonhazardous ingredients (as defined per CFR 49, 1900). However, it should be used with the same care as any industrial chemical product. Do not spray in closed or confined areas. Use with adequate (equivalent to outdoor) ventilation. Avoid breathing of vapour for prolonged periods of time. Avoid contact with eyes, skin and clothing. Do not take internally. Protective clothing such as a chemical face shield or goggles and gloves, apron and boots, made from solvent resistant materials should be worn when handling this product.

Before using this product refer to container label and HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

MARCH 2003

® Registered Tradename HENKEL Australia Pty Ltd
® Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au