



HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO® DEFLOCCULATOR 2

Material No. 377375

FOR WATER-CURTAIN PAINT SPRAY BOOTHS

DESCRIPTION:

TURCO® DEFLOCCULATOR 2 is a powder compound formulated to degenerate accumulated paint residues in water-curtain spray booth systems.

TURCO® DEFLOCCULATOR 2 is non-corrosive to ferrous metal and copper alloys and helps retard rust formation on walls, sumps, baffles and pumps normally found in water-curtain booths. TURCO® DEFLOCCULATOR 2 effectively "kills" most paints upon contact.

BENEFITS:

TURCO® DEFLOCCULATOR 2 offers these benefits:

1. Non-flammable in concentrate or solution form
2. Readily dissolves in cold water.
3. Prevents paint build upon waterwall.
4. Works at very low concentrations.
5. Easy to control by simple titration.

USE INSTRUCTIONS:

Preparation: Paint booth, tank, curtain, spray nozzles and headers should be cleaned of old paint residues prior to introducing TURCO® DEFLOCCULATOR 2. Your HENKEL Territory Manager can recommend a suitable TURCO paint remover based upon the condition of your booth.

Mixing: Fill collecting pan with fresh, cold water to its operating level. Start pump and circulate water. Add TURCO® DEFLOCCULATOR 2 at the ratio of 2.5 g/L of water. Thoroughly mix solution.

Note: Never dump large quantities of TURCO® DEFLOCCULATOR 2 into water. Always add small amounts of product onto the top of agitated water, since heat is liberated and local pockets of steam may be formed.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your local HENKEL Representative or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION:

TURCO® DEFLOCCULATOR 2 contains sodium hydroxide, petroleum solvents, silicate and carbonate. Avoid contact with skin, eyes and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, made from alkali resistant neoprene should be worn when using and handling this product.

Never dump large quantities of TURCO® DEFLOCCULATOR 2 in water. Always add small amounts of product onto the top of agitated water, since heat is liberated and local pockets of steam may be formed.

Hazardous carbon monoxide gas can form upon contact with food and beverage products in enclosed spaces and can be fatal. Follow appropriate tank entry procedure as recommended by Work Safe Australia.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

June 2002

® Registered Tradename HENKEL Australia Pty Ltd
® Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au