



**Technologies**

**TECHNICAL BULLETIN**

ABN: 82 001 302 996  
135-141 Canterbury Road, Kilsyth Victoria 3137  
Phone : (613) 9728 7200 Fax : (613) 9761 7179

## **P3 SAF-T-CLEAN 104**

### **INTRODUCTION**

**P3 Saf-T-Clean 104** is a low odour blended solvent for removal of paints and other soils from the floor in the spray booth area of an automotive assembly plant. It is usually applied by hand using a sponge, cloth or mop.

### **OPERATING SUMMARY**

<b>Chemical</b> <b>P3 Saf-T-Clean 104</b>	<b>Bath Preparation per 1,000 litres</b> Used as received
<b>Operating Control</b> No testing required	

### **THE PROCESS**

The complete process sequence normally consists of the following steps:

- A. Applying the treatment solution to the floor.
- B. Removing the paint and soils on a sponge, cloth or mop (optional).

### **MATERIAL**

**P3 Saf-T-Clean 104**

**EQUIPMENT**

None required.

**OPERATION**

Time: 5-30 minutes  
Temperature: Ambient

**STORAGE REQUIREMENTS**

It is recommended that the chemicals be stored where temperatures will not exceed 30°C.

**WASTE DISPOSAL INFORMATION**

Applicable regulations covering disposal and discharge of chemicals should be consulted and followed.

Disposal information for **P3 Saf-T-Clean 104** is supplied on the Material Safety Data Sheet.

**PRECAUTIONARY INFORMATION**

When handling **P3 Saf-T-clean 104**, in the form as supplied, the precautionary, first aid and handling recommendations on the Material Safety Data Sheet for the product should be read, understood and followed.

The cleaning solution contains petroleum solvents. Do not get in eyes, on skin or on clothing. In case of contact, follow the recommendations on the Material Safety Data Sheet for **P3 Saf-T-Clean 104**.

**DISCLAIMER**

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.