



HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO PLAUDIT

Material No. 377694

MULTI-PURPOSE LIQUID CLEANER

DESCRIPTION:

TURCO PLAUDIT is a non-hazardous water based compound formulated as a safe general purpose cleaner for use on all surfaces.

The product removes shop soils, oils, greases, road grime and lube oils from transportation, construction and drilling equipment, concrete floors, metal components, engine rooms and bilges.

TURCO PLAUDIT is currently used as a general purpose cleaner in food plants, restaurants, take away food outlets and for plant and building maintenance requirements. It is an excellent pressure washing or steam cleaning compound and is also used for hot tank immersion cleaning.

TURCO PLAUDIT is stable in acidic solutions and is used as an additive for acid brightening. This improves wetting and speeds the brightening process.

TURCO PLAUDIT's stability in seawater and its exceptional emulsification properties provides a unique replacement for solvent-based bilge cleaners and oil slick dispersal compounds. Being water based material it is less harmful environmentally and has no flash point or fire danger.

BENEFITS:

TURCO PLAUDIT offers these benefits:

1. Non corrosive safe on paint and all metals.
2. Versatile one product performs many tasks.
3. Non toxic contains no solvents, phenols, chromates or toxic ingredients.
4. Safety a non-combustible, replacement for solvent degreasers and oil slick dispersants.

USE INSTRUCTIONS:

General Cleaning: Hand wipe, mopping, high pressure cleaning and dishwashing. Add 1 part of TURCO PLAUDIT to 40 parts of warm water. Rinse surfaces with warm water if available.

Steam Cleaning: Add 1 part of TURCO PLAUDIT to each 20 parts of water in the concentrate tank. Pressure rinse with hot water if available.

Emulsion Cleaning: For spray or immersion systems, add 1 part of TURCO PLAUDIT to 5 to 10 parts of water. Clean parts at 80 to 90°C. Rinse with warm overflowing water or by pressure spray.

Ultrasonic Cleaning: Add 10 ml of TURCO PLAUDIT per litre of water. Operate ultrasonic equipment per manufacturer's instructions.

Bilge Cleaning: Add 20 litres of TURCO PLAUDIT each 1000 Litres of Bilge Water.

Oil Slick Dispersal: Mix with 1 to 2 parts water and spray directly over oil slick.

DISPOSAL INFORMATION:

Dispose of spent solution as per local, state and regional regulations. Refer to your local HENKEL Representative or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION:

The ingredients used in TURCO PLAUDIT are considered to be non-hazardous, as defined by the N.H. & M.R.C. However, as in the case of any chemical compound, avoid contact with eyes, skin and clothing. Do not take internally.

Refer to container label, HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

MARCH 2003

® Registered Tradename HENKEL Australia Pty Ltd
© Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au