



Surface
Technologies

HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO PRECHEK LF

Material. No. 381776

DYCHEK AEROSOL PRE-CLEANER (STEP 1)

DESCRIPTION:

TURCO PRECHEK LF is a clean, colourless liquid formulated for precleaning surfaces prior to penetrant inspection.

TURCO PRECHEK LF also removes grease, pencil marks, ink marks, oil and grease from parts and is ideal for touch-up cleaning of parts prior to packaging where a quick, fast evaporative cleaner is desired.

TURCO PRECHEK LF should not be used on materials that are affected by aliphatic hydrocarbons.

As TURCO PRECHEK LF is highly flammable and must not be used where ignition is possible. For electrical applications WHITESOLV EC is recommended.

TURCO PRECHEK LF is currently listed in the latest QPL to Mil-C-25135 D and E.

BENEFITS:

TURCO PRECHEK LF offers these benefits:

1. Quickly evaporates to residue-free dryness.
2. Used as received at room temperature.
3. Applied by dip, wipe or non-atomising spray methods.
4. Stable product, requires no mixing.

USE INSTRUCTIONS:

Spray direct from the can until surface is clean. Do not spray without adequate ventilation. Ensure no ignition sources are present as PRECHEK LF is highly flammable.

DISPOSAL INFORMATION:

Dispose of cloths and spent solution per local, state and regional regulations. Refer to your local HENKEL REPRESENTATIVE, or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION:

TURCO PRECHEK LF contains aliphatic petroleum solvent. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid prolonged breathing of fumes.

Protective clothing, such as chemical face shield or goggles, gloves, boots and apron made from solvent resistant neoprene should be worn when handling and using this product.

Do not use TURCO PRECHEK LF near open flames, cutting torches or welding arcs, since material has a Pensky Marten flash point of -4°C.

Do not store containers above 50°C or near strong oxidising agents. Use care in opening drums to avoid spurting of contents.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

JUNE 2002

® Registered Tradename HENKEL Australia Pty Ltd
© Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au