



HENKEL Australia Pty Ltd  
A.C.N. 001 302 996

135-141 Canterbury Road  
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200  
Fax: (03) 9728 5877  
Customer Service 1300 736 777

Distributed by  
Solvents Australia Pty Ltd  
ABN 74 003 523 117  
77 Bassett Street  
Mona Vale NSW 2100  
PO Box 928  
Mona Vale NSW 1660

Tel: (02)9979 6866  
Fax: (02)9979 6864

---

## Technical Data Bulletin

---

### TURCO SPRAYEZE

Material No. 382770

#### HEAVY DUTY SPRAY AND IMMERSION CLEANER FOR FERROUS AND NON-FERROUS ALLOYS

##### DESCRIPTION:

TURCO SPRAYEZE is a high performance medium alkaline spray washing compound formulated to remove heavy contaminations of oil, grease, drawing lubricants and general soils from auto parts and metal components during manufacture.

TURCO SPRAYEZE is widely used by auto engine reconditioners and transmission repair specialists as a hot spray washing compound. A major plus for this product is that when used as directed parts do not flash rust after use.

##### BENEFITS:

TURCO SPRAYEZE offers these benefits:

1. Safe on paint and all metals.
2. Can be used in spray or immersion systems.
3. Very free rinsing.
4. Non-foaming at recommended concentration and temperature.
5. Free of caustic soda.
6. Heavily inhibited to prevent flash rusting.

##### USE INSTRUCTIONS:

TANKS: Tanks and associated equipment may be fabricated from mild steel or stainless steel.

##### SPRAY SYSTEMS:

Mixing: Add TURCO SPRAYEZE to warm, circulating water at the ratio of 12-18 g/L. Clean parts at 80-90°C for 1 to 3 minutes at a spray pressure of 30 to 50 psi.

Rinsing: Rinse with warm to hot water spray for 30 seconds to 2 minutes.

##### IMMERSION SYSTEMS:

**Mixing:** Add TURCO SPRAYEZE to warm, agitated water at the ratio of 40-50 g/L. Clean parts with air or mechanical agitation at 80-90°C for 5 to 10 minutes.

**Note:** For use with "THERMOJET" Units use at 6-12 g/L. Regular solution replacement obviates need for rinsing.

**DISPOSAL INFORMATION:**

Dispose of spent solution per local, state and regional regulations. Refer to your local HENKEL Territory Manager, District Sales Office or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

**CAUTION:**

TURCO SPRAYEZE contains sodium silicate and sodium chromate. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, boots and apron, made from alkali resistant neoprene should be worn when using and handling this product.

Ship and store in closed containers away from excessive heat or direct sunlight.

Refer to container label, HENKEL MATERIAL SAFETY DATA SHEET or local HENKEL office for additional precautionary, handling and first aid information.

**JUNE 2002**

® Registered Tradename HENKEL Australia Pty Ltd  
© Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: [admin@solvents.net.au](mailto:admin@solvents.net.au)