



TURCO 5948 DPM THICK

ENVIRONMENTALLY ACCEPTABLE THIXOTROPIC, WATER BASE, HEAVY DUTY AIRCRAFT CLEANER

1. DESCRIPTION:

TURCO® 5948 DPM THICK is a viscous alkaline, water base, blue, concentrated compound formulated to effectively cling to painted and unpainted aircraft exterior and interior surfaces.

TURCO® 5948 DPM THICK is ideally suited for use in all jets, especially in baggage bins, flap and wheel areas, and on engines before overhaul.

2. BENEFITS:

TURCO® 5948 DPM THICK offers these features:

1. Effectively removes jet soils, such as synthetic oil films, grease, carbon and exhaust residues from aircraft exterior surfaces, landing gears, wheel wells, flaps, engine, etc.
2. For use on all aircraft metals and well bonded paint.
3. Non-staining and non-streaking to aluminium.
4. Non-crazing to Plexiglass.
5. Conforms to Douglas CSD #1 and Pratt and Whitney SPOP #1.
6. Very free rinsing.
7. Multi-purpose, exterior and interior cleaning.
8. Pleasant and refreshing odour.
9. Non-flammable.
10. Does not contain phosphates, chromates, butyl cellosolve, or heavy aromatic solvents.
11. Will not attack asphalt ramps.

3. USE INSTRUCTIONS:

- a. **Heavy Duty and General Purpose Cleaning:** For accumulations of oil, grease, carbon and traffic soils use as received. Apply by spray or mop. Spraying may be accomplished with a **TURCO®** BARREL PUMP or Sprayer. Allow to dwell and agitate surface with mops or soft bristle brushes. Follow with a pressure rinse of clean tap water or steam.
- b. For immersion cleaning **TURCO® 5948 DPM THICK** may be diluted 1 part cleaner with 3 to 20 parts water. Use at 65°C - 80°C for 5-15 minutes.

4. DISPOSAL INFORMATION:

Dispose of **TURCO® 5948 DPM THICK** per local, state and regional regulations. Refer to your HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! Causes eye irritation. May cause skin irritation.

TURCO® 5948 DPM THICK contains ethanalamine. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron, made from alkali-resistant materials should be worn when using and handling this product.

Before using this product refer to container label and HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.